



TBS COMPONENT DATA SHEET

TECHNICAL BARRIER SYSTEMS INC.



TEL: 905.842.9488 FAX: 905.842.1582 TOLL FREE: 1.888.537.2888
 EMAIL: MAIL@TBSPRODUCTS.COM WEB: WWW.TBSPRODUCTS.COM

1328 HS ADHESIVE

PARQUET WOOD FLOOR BONDING AGENT

Description

1328 HS Adhesive is specially formulated for the parquet floor wood industry for bonding wood parquet flooring to concrete and other substrates. This high strength, waterborne, polymeric mastic adhesive is free of 1, 1, 1 Trichloroethane, reducing potential fire and safety hazards. In addition, it is easy to spread and offers good open time for more professional installation.

- Vacuum entire surface thoroughly
- Stir well before using. Before walking on installed area, allow the adhesive to dry overnight
- Before applying on basement floors or areas below ground level, make sure that the area is dry and free of moisture problems
- When stored at room temperature, will have a shelf life of one year

Typical Uses

- Dry concrete (above or on grade)
- Standard plywood underlayment
- Terrazzo
- Wood Parquet Flooring
- Portland cement underlayment
- Gypsum cement underlayment

Features

- High Strength
- Easy Spreading Quality
- Safe, solvent free chemistry
- Water based polymeric mastic formulation
- Soap and water cleanup
- Low Odor

Limitations

- Do not freeze

Application

- Apply at temperatures between 50°F to 100°F (10°C to 38°C)
- Scrape off all foreign matter and ensure that the surface is clean of dust, oil and wax

Physical Properties

Initial Tack Time	30 minutes
Viscosity	54,000 cps
Percent Solids	70%
ASTM C 882	311.25 psi
	2.15 MPa
ASTM C 882 (Wet)	113.75 psi
	0.784 MPa

Packaging

Available in 1-gallon (3.75 Litres) pails, and 5-gallon (18.9 Litres) pails.

Coverage

- Approximately 80 square feet per gallon

Pot Life

- 1 – 2 hours

Safety Precautions

Please refer to product MSDS Sheet. Page 1 of 1