



TBS COMPONENT DATA SHEET

TECHNICAL BARRIER SYSTEMS INC.



TEL: 905.842.9488 FAX: 905.842.1582 TOLL FREE: 1.888.537.2888
EMAIL: MAIL@TBSPRODUCTS.COM WEB: WWW.TBSPRODUCTS.COM

#151 AGGREGATE

Description

#151 Aggregate is reprocessed rubber based aggregate used with the EMBE® Merdek System and with the Kelmar® P.C. Joint Detailing. #151 aggregate is a consistent quality, flexible aggregate with resilient durability. It is safe and non-toxic.

Features

- 100% recycled material
- Slip resistant
- Can be applied over various substrates
- Flexible

Limitations

- All substrates must be sound and clean and free from contaminants
- Substrate temperature must be between 50°F (10°C) and 90° F (32° C)

Mix Ratio

- 1.5 gallons #151 Aggregate per 2 gallons of Merdek Basecoat or 2 gallons of Kelmar PC Wearcourse. Applied by notched trowel or gage rake. (mix ratio may be adjusted for ease of application)

Storage

- Store in a safe dry place 50°F - 90° F.

Safety Precautions

- Please refer to the product Material Safety Data Sheets (MSDS)

Physical Properties

Appearance and odour	Black granules
Specific Gravity	1.14+/-0.03
Auto Ignition Temperature	700 F
Flash Point	475 F
Stability	Stable
Solubility in Water	Nil